



FINISHED SURFACE LEVEL TOLERANCES

SITUATION	TOLERANCES
IN ROAD RESERVE INCLUDING SEALED PAVEMENTS, ROAD VERGES DRIVEWAYS, FOOTPATHS, PEDESTRIANS THOROUGHFARES.	+10 mm HIGH - 5 mm LOW
SEALED AND TRAFFICABLE AREAS WITHIN PRIVATE PROPERTIES. (PEDESTRIAN AND/OR VEHICULAR TRAFFIC)	+15 mm HIGH - 5 mm LOW
IN PRIVATE PROPERTY INCLUDING GARDEN AREAS, UNSEALED AREAS, NON-TRAFFICABLE AREAS OR AREAS OF OCCASIONAL TRAFFIC (PEDESTRIAN AND/OR VEHICLE TRAFFIC)	+20 mm HIGH - 5 mm LOW

NOTES:

1. REFER 4005-20002-01 TO 4005-20002-03 FOR GENERAL NOTES.
2. REFER 4005-20005-03, NOTE 2 FOR INSTRUCTIONS REGARDING COMPONENTS.
3. APPROVED METHODS OF ACHIEVING THE REQUIRED FINISHED LEVEL (FSL) ARE PRESENTED ON THIS DRAWING.

REVISION PANEL

REV	DATE	DRN	DETAILS	APR
1	31/03/16	MS	2016 STANDARDS REVIEW	TG

DESIGN PANEL

DESIGNED: 03/08/15	AUTHORISED: 31/03/16
RJP	T.GALEK
DRAWN: 25/09/15	SIGNATURE:
MS	
REVIEWED: 21/03/16	
TG	



This drawing is the property of the
SOUTH AUSTRALIAN
WATER CORPORATION
and shall not be copied or modified
in part or in whole without authorization.

SA WATER STANDARD DRAWINGS SEWER CONSTRUCTION MANUAL MAINTENANCE HOLE LID ADJUSTMENT TYPICAL DETAILS

A3	1
SHT SIZE	REVISION
TOTAL SHEETS:	
SUPERSEDES: L5, L6, L15	
DRAWING NUMBER	
4005-20005-04	
PREFIX	NUMBER SHEET